


HunterDouglas

SUN CONTROL



For many years Hunter Douglas has built folding shutters in projects as manual or motorized sun control solution. Folding shutters give a strong dynamic effect to a building by radically changing the facade from a closed, monolithic volume to an open, transparant envelope. The panels fold away from the façade, literally creating an extra dimension that makes this transformation even more dramatic.

With these years of experience Hunter Douglas has also been able to achieve an important technical feat: a motorized folding shutter that will close completely flat. A specially engineered clever hinge mechanism operated by a compact linear actuator enables the shutter to meet the logical expectation of user and architect to fold away completely in the façade surface.




HunterDouglas




HunterDouglas® Folding Shutters are typically built in aluminium with either fixed louvre fins or a perforated aluminium sheet panel, but can also be provided with any custom material. This allows a complete integration in the surrounding façade. Shutter width can vary from 530 to 900 mm and shutter height can be up to 3600 mm, depending on situation and wind load.

DIMENSIONS


The maximum dimensions of the folding shutter depend on the applicable wind loads. The table on the right shows the maximum allowable wind load for different shutter widths and heights.








For fins there is a choice of three aluminium fin types; for perforated sheet there is a choice of two functional perforation patterns with 5% or 10% open area for visual and thermal interior comfort. Application of custom design perforations or patterns is also possible. Finish can be anodized or powdercoated in any available




colour. The HunterDouglas® Folding Shutter is fully weather resistant and requires only a minimum of maintenance.

FOLDING SHUTTER - KEY FEATURES

- Folding shutter with aluminium fins or perforated sheet
- Manually operated or motorized, both closing completely flat
- Changes façade appearance instantly from closed to open
- Available as single pair (V) or double pair (W, manual only)
- Filters direct sunlight, allows outward view and reduces solar radiation impact by 90%
- Totally weather resistant and virtually maintenance free
- Clever hinge mechanism operated by 24V actuator
- Designed for easy and safe installation
- Two perforation options and three fin options offered as standard
- Custom design perforations or materials possible
- Unlimited choice of colours



















Belgium

Bulgaria

Czechia

France

Hungary

Poland

Portugal

United Kingdom

Middle East

Asia

Australia

Latin America

North America

HUNTER DOUGLAS EUROPE B.V.

2, Piekstraat

P.O. Box 5072 - 3008 AB Rotterdam

The Netherlands

Tel. +31 (0)10 - 486 99 11

Fax +31 (0)10 - 484 79 10

www.hunterdouglascontract.com

HunterDouglas

WINDOW COVERINGS CEILINGS

SUN CONTROL

FAÇADES

® Registered trademark - a HunterDouglas® product Pats. & Pats. Pend. - Technical data subject to change without notice. © Copyright Hunter Douglas 2014. No rights can be derived from copy, text pertaining to illustrations or samples. Subject to changes in materials, parts, compositions, designs, versions, colours etc., even without notice.